

Major Specifications

Number of doors	5		
Engine	Petrol 1.5L		
Drive system	ALLGRIP PRO		
Transmission	5MT	4AT	
DIMENSIONS			
Overall length	Front bumper to rear bumper	mm	3,820
Overall width		mm	1,645
Overall height		mm	1,720
Wheelbase	Front	mm	2,590
Tread	Rear	mm	1,395
		mm	1,405
Minimum turning radius		m	5.7
Minimum ground clearance		mm	210
Approach angle		deg.	36
Ramp breakover angle		deg.	24
Departure angle		deg.	47
CAPACITIES			
Seating capacity	Max. volume	persons	4
Luggage capacity	Rear seatback folded (VDA method)	litres	1,113
	Rear seatback raised (VDA method)	litres	332
		litres	211
Fuel tank capacity		litres	40
ENGINE			
Type	K15B		
Number of cylinders	4		
Number of valves	16		
Piston displacement	cm ³	1,462	
Bore x stroke	mm	74.0 x 85.0	
Compression ratio	10		
Maximum output	kW/rpm	75/6,000	
Maximum torque	N·m/rpm	130/4,000	
Fuel distribution	Multipoint injection		
TRANSMISSION			
Type	5MT 4AT		
Gear ratio	1st	4.425	2.875
	2nd	2.304	1.568
	3rd	1.674	1.000
	4th	1.190	0.697
	5th	1.000	-
	Reverse	5.151	2.300
Final gear ratio	4.090 4.300		
Transfer gear ratio	High	1.000	1.320
	Low	2.002	2.643
CHASSIS			
Steering	Recirculating ball		
Brakes	Front	Ventilated disc	
	Rear	Drum, leading and trailing	
Suspension	Front	3-link rigid axle with coil spring	
	Rear	3-link rigid axle with coil spring	
Tyres	195/80R15		
WEIGHTS			
Kerb weight (min./with full options)	kg	1,185-1,205	1,200-1,215
Gross vehicle weight	kg	1,545	1,545
PERFORMANCE			
Maximum speed	km/h	155	140

All figures are manufacture's data and may vary for each market.

For information about official certification data, please contact the SMC marketing group in charge of your area.

