

Major Specification

Number of doors		3	
Engine		Petrol	
		1.5L VVT	
Drive system		Part-time 4WD (ALLGRIP PRO)	
Transmission		5MT	4AT
DIMENSIONS			
Overall length	Front bumper to rear bumper	mm	3,480
	Front bumper to spare wheel	mm	3,625
Overall width		mm	1,645
Overall height		mm	1,725
Wheelbase		mm	2,250
Tread	Front	mm	1,395
	Rear	mm	1,405
Minimum turning radius		m	4.9
Minimum ground clearance		mm	210
Approach angle		deg.	37
Ramp breakover angle		deg.	28
Departure angle		deg.	49
CAPACITIES			
Seating capacity		persons	4
Luggage capacity	Max. volume	litres	830
	Rear seatback folded (VDA method)	litres	377*
	Rear seatback raised (VDA method)	litres	85*
Fuel tank capacity		litres	40
ENGINE			
Type			K15B
Number of cylinders			4
Number of valves			16
Piston displacement		cm ³	1,462
Bore x stroke		mm	74.0 x 85.0
Compression ratio			10
Maximum output		kW/rpm	75/6,000
Maximum torque		N-m/rpm	130/4,000
Fuel distribution			Multipoint injection
TRANSMISSION			
Type			5MT 4AT
Gear ratio	1st		4.425 2.875
	2nd		2.304 1.568
	3rd		1.674 1.000
	4th		1.190 0.697
	5th		1.000 -
	Reverse		5.151 2.300
Final gear ratio			4.090 4.300
Transfer gear ratio	High		1.000 1.320
	Low		2.002 2.644
CHASSIS			
Steering			Recirculating ball
Brakes	Front		Solid disc
	Rear		Drum, leading and trailing
Suspension	Front		3-link rigid axle with coil spring
	Rear		3-link rigid axle with coil spring
Tyres			195/80R15
WEIGHTS			
Kerb weight (min./with full options)		kg	1,090/1,135 1,110/1,135
Gross vehicle weight		kg	1,435
PERFORMANCE			
Maximum speed		km/h	145 140

All figures are manufacture's data and may vary for each market
* Measured without luggage box.

